

MATERIAL SAFETY DATA SHEET

Product name: Catalog number:

Biotin Labeling Kit-SH KA0004

1. Composition/Information on Ingredients

Component	Size
SH-Reactive Biotin	3 tubes
Reducing Agent	3 tubes
WS buffer	4 ml x 1
Reaction buffer	1 ml x 1
Filtration tube	3 tubes

2. Hazards Identification

Known Hazardous Components	CAS Number	Percent
Glycerol	56-81-5	
Washing Buffer		< 50 %

3. First Aid Measures

First aid personnel should ensure self-protection.

General information: Because of the low concentrations of the ingredients seeing a doctor is not necessary.

In case of skin contact: Immediately wash skin with soap and copious amounts of water. Assure adequate flushing

of the eyes by separating the eyelids with figures.

In case of eye contact: Immediately flush eyes with plenty of water for at least 15 minutes.

In case of ingestion: Wash out mouth with water. .

In case of inhalation: Remove to fresh air. Of not breathing, give artificial respiration. If breathing is difficult, give

oxygen.

4. Fire Fighting Measures

Flash Point (Method Used): Not available

Biotin Labeling Kit-SH (Cat # KA0004)



Flammable Limits: Not available

Extinguishing Media: Carbon dioxide, dry chemical powder, foam, water.

Special Fire Fighting procedures:

Wear protective clothing, respirator, chemical safety goggles, rubber boots and heavy rubber gloves. Unusual Fire and

Explosion Hazards: Fire may produce irritating or poisonous gases.

5. Accidental Release Measures

Steps to be taken in Case Material is Released or Spilled:

Wear self— contained breathing apparatus, rubber boots and heavy rubber gloves. Evacuate area. Sweep up, place in a bag and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete. Avoid raising dust.

6. Handling and Storage

Wear appropriate NIOSH/MSHA-approved respirator, chemical-safety goggles, chemical-resistant gloves, other protective clothing. Mechanical exhaust required. Used only in a chemical fume hood. Safety shower and eye bath. Face shield. Do not breathe dust. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling. Irritant. Harmful solid. Avoid all contact. Avoid prolonged or repeat.

Other precautions:

Keep tightly closed. Protect from moisture. Store in a cool(0-5°C) dark and dry place..

7. Exposure controls/personal protection

Respiratory Protection (Specify Type): Necessary

Ventilation, Local Exhaust: Chemical fume hood

Mechanical (General): Necessary

Protective Gloves: Chemical-resistant gloves

Eye Protection: Chemical-safety goggles

Other protective Clothing or Equipment: Necessary

Work/Hygienic Practices: Wash thoroughly after handling. Access to a safety shower and

eye-wash. Do not permit eating, drinking or smoking near materials.

8. Physical and Chemical Properties

Melting POint: N/A

Boiling Point: N/A

Specific Gravity (water=1): N/A

Vapor Pressure: N/A

Vapor Density (air=1): N/A

Evaporation Rate (butyl acetate=1): N/A



Solubility: Soluble in DMSO

Appearance and Odor: White powder (SH-Reactive Biotin and Reducing Agent)

Colorless solution (WS buffer and reaction buffer)

9. Stability and Reactivity

Stability: Stable

Conditions to Avoid: Heat, sunlight, high temperature

Incompatibility (Materials to Avoid): Strong oxidizing agents, strong acids and strong bases.

Hazardous decomposition or Byproducts: When decomposed, it may emit toxic fumes of carbon monoxide, carbon dixide,

nitrogen oxides and sulfur oxides, phosphorus oxides and hydrogen chloride gas.

Hazardous Polymerization: Will not occur

10. Toxicological Information

Not available.

11. Ecological information

No data available.

12. Disposal guidelines

Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with and afterburner and scrubber.

13. Transport information

Not available.

14. Regulatory information

Not available.

15. Other

The above information is believed to be correct does not purport to be all inclusive and shall be used only as a guide.

We shall not be held liable for any damage resulting from handling or form contact with the above material.