



# SZABO SCANDIC

Part of Europa Biosite

## Produktinformation



Forschungsprodukte & Biochemikalien



Zellkultur & Verbrauchsmaterial



Diagnostik & molekulare Diagnostik



Laborgeräte & Service

Weitere Information auf den folgenden Seiten!  
See the following pages for more information!



### Lieferung & Zahlungsart

siehe unsere [Liefer- und Versandbedingungen](#)

### Zuschläge

- Mindermengenzuschlag
- Trockeneiszuschlag
- Gefahrgutzuschlag
- Expressversand

### SZABO-SCANDIC HandelsgmbH

Quellenstraße 110, A-1100 Wien

T. +43(0)1 489 3961-0

F. +43(0)1 489 3961-7

[mail@szabo-scandic.com](mailto:mail@szabo-scandic.com)

[www.szabo-scandic.com](http://www.szabo-scandic.com)

[linkedin.com/company/szaboscandic](https://www.linkedin.com/company/szaboscandic) 

# PowerWave™ HT Microplate Spectrophotometer

The PowerWave™ HT incorporates fast 96- and 384-well microplate reading and high performance optics into a very compact footprint, ideal for integration into automated systems. PowerWave HT also features a 200 – 999 nm wavelength range for filter-free wavelength selection.

BioTek's exclusive 4-Zone™ natural convection incubation and user programmable shaking profiles round out the outstanding feature set available in PowerWave HT. Gen5™ Microplate Reader and Imager Software provides unprecedented ease of use along with powerful data reduction and output options.



PowerWave™ HT with BioStack™  
Microplate Stacker



## Features:

- 96-well measurements in as little as 5 seconds
- 200 – 999 nm measurements
- 96- and 384-well plate compatibility
- Automated pathlength correction
- Precise 4-Zone™ temperature control
- Robust hardware designed for rigorous use in automated systems
- Gen5 software included
- BioStack™ and 3rd party automation compatibility

## Typical Applications:

- Enzyme kinetics
- ELISA
- Genetic analysis by colorimetry
- Cellular analysis by colorimetry
- Cell proliferation

## Configurations:

RPRWI: High throughput, 8-channel microplate spectrophotometer

## Optional Accessories:

- BioStack™ Microplate Stacker
- Gen5™ Secure for 21 CFR Part 11 Compliance
- Product Qualification Package
- Absorbance Test Plate
- Patented BioCell™ 1 cm cuvette (and adapter)
- Adapter plate for 1 cm stoppered cuvettes

## Specifications:

### General

Detection method:	Absorbance
Read method:	End point, kinetic, spectral, linear scanning
Microplate types:	96 and 384 wells
Temperature control:	4-Zone™ incubation to 50 °C
Shaking:	Yes
Software:	Gen5™ Microplate Reader and Imager Software
Automation:	Compatible with BioStack and 3rd party automation

### Absorbance

Light source:	Xenon flash lamp
Wavelength selection:	Monochromator, selectable 1 nm or greater increments
Wavelength range:	200 – 999 nm
Bandpass:	5 nm
Dynamic range:	0 – 4.0 OD
Resolution:	0.001 OD
Monochromator wavelength accuracy:	±2 nm
Monochromator wavelength repeatability:	±0.2 nm
OD accuracy:	1% ±0.01 OD
OD linearity:	±1%
OD repeatability:	0.5% ±0.005 OD
Stray light:	0.03% at 230 nm
Reading speed:	96 wells: 5 seconds 384 wells: 11 seconds

### Physical Characteristics

Power:	100 – 240 Volts AC. 50/60 Hz
Dimensions:	16"D x 8.5"W x 8.5"H (40.6 x 21.6 x 21.6 cm)
Weight:	24 lbs (11 kg)

### Regulatory

CE and TUV marked, RoHS compliant. In Vitro Diagnostic use configurations available.

*Performance values represent the average observed factory test values.*

*\*Specifications subject to change.*

Rev. 07/07/16



**BioTek Instruments, Inc.**  
Highland Park, P.O. Box 998  
Winooski, Vermont 05404-0998, USA

Phone: 802-655-4040 • Toll-Free: 888-451-5171  
Outside the USA: 802-655-4740  
[www.biotek.com](http://www.biotek.com)